Your Connection to Network.

A-LINK®

A-LINK SD24-2G
24 PORT 10/100Mb SWITCH
2 PORT 1000Mb UPLINK

24-port 10/100MB Switch with MDI-X autosensing ports and 2pcs gigabit uplink ports.
Product is CE and FCC approved.
A-LINK Retail package contains switch, power supply and installation guide.

Product specification :

• Standards

IEEE 802.3 10BASE-T
IEEE 802.3u 100BASE-TX
IEEE 802.3x
IEEE 802.3ab 1000BASE-T

• Autosence

Auto-MDI/MDIX detects and corrects cabling errors.

• MAC address

4096

• Buffer memory

3Mb buffer
1Mb Adress table memory

• Forwarding mode

Store-and-forward

• Interface

24 x 10/100 Mbps RJ-45 ports
2x 10/100/1000 Mbps RJ-45 uplink ports

• Transmission mode

Half or full duplex

• Protocol

CSMA/CD

• Uplink

2 pcs 10/100/1000Mb uplinks

• Flow control

Back pressure, IEEE 802.3x

• Panel indicators

Per unit: power
Per port: link/activity/,10/100M indication, half/full duplex

• Compliance

CE and FCC

• A-LINK Retail package contains :

- Switch
- Power cable
- Installation guides

• Package info :

Export cartoon size 5pcs

• Ean / Order code :

6418949026267

A-LINK is a registered trademark of A-LINK.
http://www.a-link.com SD24-2G specs UK 12.11.08
All rights reserved